



COMPACTORS

HUSQVARNA LT 6005

Art.no: 967 85 45 04


LT 6005 is a well-balanced and powerful rammer, developed for efficient compaction of granular and cohesive soils such as clay and silt. Ideal for compaction in trenches or other narrow spaces, for example around pillars and pipes. Equipped with the latest Honda GXR120 engine, which is especially designed for rammers. The rammer offers superb control, low noise and low emissions.

FEATURES



High compaction performance

Efficient compaction thanks to a powerful Honda engine mounted in a compact, durable chassis delivering high speed and high impact force.



Great ergonomics

The single lifting point and rollers on the steering bow make on-site handling easy. Transport wheel kit available as an accessory.



Easy to manoeuvre

The three-position throttle control (idle, full speed, stop/closed) also closes the fuel line to prevent leakage. The balanced design provides excellent traction and maneuverability.



Easy to service

Easy access to all service points including oil level checking (engine and foot), air filter cleaning/replacing. Equipped with hour meter, air filter indicator and oil warning indicator.

TECHNICAL DATA HUSQVARNA LT 6005

Art.no: 967 85 45 04

HUSQVARNA LT 6005

ENGINE

Motor/engine model	GXR 120
Engine Power (As rated by the engine manufacturer)	2.7 kW
Power/fuel type	Petrol
Exhaust emissions (CO, EU V)	674 g/kWh
Power source	Petrol

PRODUCT DATA

Speed	16.5 m/min
-------	------------

DIMENSIONS

Plate width	230 mm
Product size length	726 mm
Product size width	345 mm
Product size height	1,084 mm
Weight (complete product w/o side packed articles)	68 kg
Packaging length	1,100 mm
Packaging width	450 mm
Packaging height	970 mm
Article gross weight	79,500 g

SOUND AND NOISE

Sound power level, guaranteed (LWA)	106 dB(A)
Sound pressure level at operators ear (LpA)	92 dB(A)



View all product details on:

<https://www.husqvarnaconstruction.com/in/compactors/lt6005/>