



DEMOLITION EQUIPMENT

HUSQVARNA DXR 275

Art.no: 970 51 74 01

DXR 275 is a compact remote-controlled demolition robot with low weight and 24 kW power. Thanks to its high power-to-weight ratio it is ideal for demolition work at construction sites with low ground pressure or limited lifting possibilities. The arm delivers precise positioning of the tool and only requires minimal servicing. The outriggers are individually controlled and combined with a large footprint providing superior stability which enables high workload. Equipped with a superior remote control for safer operation and easy maneuverability. DXR 275 is a versatile demolition robot for both the construction and process industry. Combine it with a variety of tools like hammers or our compact and versatile crushers and steel shearer. For the toughest applications we recommend our additional feature packages. For DXR 275 we offer extended hydraulic function and cylinder protection package, enhanced cooling and heat protection. This enables you to work with the machine in high ambient temperatures and with the tool in a high radiation heat. The packages can be ordered as accessories or installed direct from the factory.

FEATURES



Increased performance

More than 20% increased performance in power, higher productivity and efficiency.




Safer operation

Fulfills third party approval in respect of EMC, functional safety requirements and high reliability levels (PLd) which ensures a safer work environment.



Superior remote control

Enables a pleasant experience and good operational control with high level of intuitive user-friendliness with large screen with optimised angle and adaptable to dark and bright surroundings. Enables you to work remote-controlled in the most challenging areas from a distance up to 300 m.



Live operating surveillance

The remote control delivers live information about machine status such as current, voltage, temperature as well as active faults and operating time without the need of external measuring equipment. For instant machine status, increased uptime and productivity.

TECHNICAL DATA HUSQVARNA DXR 275

Art.no: 970 51 74 01

HUSQVARNA DXR 275

MOTOR

Rated input power	24 kW
Frequency	50/60 Hz

BATTERY

Battery chemistry	Li-Ion
-------------------	--------

HYDRAULICS

Oil capacity	42 l
Hydraulic oil flow	75 l/min
Hydraulic pressure, max	250 bar

OTHER

Factory option	Standard
Telescopic arm	No
Range of wireless transmission	Up to 300 m
Signal transmission	Radio/cable
Radio	2.4 GHz

DIMENSIONS

Reach (up)	4.8 m
Reach (forward)	4.5 m
Product size length	2,442 mm
Product size width	780 mm
Product size height	1,367 mm
Weight (complete product w/o side packed articles)	1,850 kg
Packaging length	3,030 mm
Packaging width	950 mm
Packaging height	1,920 mm
Article gross weight	22,77,000 g



View all product details on:

<https://www.husqvarnaconstruction.com/in/demolition-equipment/dxr275/>



DEMOLITION ROBOT TOOLS
MG 200

Jaw opening, max:
900 mm

Weight (complete product w/o side packed articles):
169 kg

Volume:
70 l

Rotation angle:
360 °



DEMOLITION ROBOT TOOLS
SB 202

Impact energy:
406 Joule

Weight (complete product w/o side packed articles):
210 / 216 / 223 kg

Hydraulic oil flow:
66 l/min

Product size width:
16.1 / 410 mm



DEMOLITION ROBOT TOOLS
DCR 300

Jaw opening, max:
430 mm

Weight (complete product w/o side packed articles):
274 kg

Crushing force:
45 t

Cutting force:
143 t



DEMOLITION ROBOT TOOLS
DSS 200

Jaw opening, max:
200 mm

Weight (complete product w/o side packed articles):
185 kg

Cutting force:
85.7 t

Rotation angle:
360 °



DEMOLITION ROBOT TOOLS
ER 50

Weight (complete product w/o side packed articles):
190 kg

Rotation angle:
360 °

Hydraulic oil flow:
60 l/min

Product size width:
500 mm



[husqvarnaconstruction.com](https://www.husqvarnaconstruction.com)