

Husqvarna DXR 140

DXR 140 is our most compact remote-controlled demolition robot with a 360 degrees rotatable arm. With 15 kW power and low weight it is a powerful machine specially developed for demolition work in cramped spaces where the job requires a manoeuvrable and compact machine with high demand of demolition efficiency. DXR 140 is a versatile demolition robot for the construction and process industry. Combine it with a variety of tools like hammers or our compact and versatile crushers and steel shearer. For DXR 140 we recommend our cylinder protection additional package. The package can be ordered and installed directly from the factory or as separate accessory.

- Reach (up) **3.7 m**
- Reach **3.7 m**
(forward)

Article number : DEMOLITION ROBOT DXR

140 15 kW | Hydraulic Track Tension - 966 52

93-02



FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



Superb power-to-weight ratio

Compact and powerful in relation to the low weight. Its large footprint enables a high workload.



Fits through all normal doorways

With a compact design, only 77 cm in width the machine can access many working locations.

360 degrees rotatable arm

With reduced need to move the machine you minimise set-up time and can easily operate in confined spaces.

- Precise positioning
- Superior stability
- Stable arm with low maintenance
- Comfortable operation
- Flexible set-up of individually parameters
- High work efficiency
- User-friendly remote control

Compact design and low weight

Gives good access to confined spaces and high manoeuvrability.

- Safer operation
- Easy transportation
- Easy access for servicing
- Casted baseplate in one piece
- Unbeatable illumination
- Automatic greasing of the breaker
- Hydraulic feature P1 installed from factory

SPECIFICATIONS



Battery

Battery capacity

Battery type

2.25 Ah

Li-Ion

Specifications

Telescopic arm

Range of wireless transmission

Signal transmission

Radio

No

Up to 100 m

Radio or cable

**Industrial Bluetooth,
class 1**

Hydraulics

Oil capacity

Hydraulic oil flow

Hydraulic pressure, max

28 l

52 l/min

250 bar



Dimensions

Reach (forward)

Reach (up)

Product size length

Product size width

Product size height

Weight

3.7 m

3.7 m

1932 mm

771 mm

1215 mm

967 kg