



Husqvarna®



COMPACTORS

HUSQVARNA LP 6500

Art.no: 967 96 67 01

LP 6500 is a fully hydraulic duplex roller, developed for compacting thin layers of granular soil and asphalt. High centrifugal force and speed increases productivity, while the sleek, compact design allows easy handling close to walls and in confined spaces. It comes equipped with a Kohler KD 441 diesel engine, built-in hydraulic oil cooler and features an ergonomic, service-friendly design.

FEATURES



Work anywhere

The compact design with high curb clearance on both sides, no overhang and sleek sides allows you to get close to walls, posts or edges – basically anywhere your work may take you.



Hours of efficient work

The vibration-damping handle features an easy to use vibration control. This makes switching the vibration on and off simpler, so you can work longer.



Longer service life

Built-in hydraulic oil cooler reduces wear and extends the lifetime of components, increasing reliability in tough, hot conditions.



Effective engine

The powerful Kohler KD 441 diesel engine delivers low fuel consumption and low emissions. It also features an hour meter and oil alert for optimal control.

TECHNICAL DATA HUSQVARNA LP 6500

Art.no: 967 96 67 01

HUSQVARNA LP 6500

ENGINE

Engine Power (As rated by the engine manufacturer)	5.6 kW
Starter	Electric
Exhaust emissions (CO, EU V)	987 g/kWh
Power source	Diesel

PRODUCT DATA

Centrifugal force	20 kN
Speed	55.5 m/min

DIMENSIONS

Product size length	2,551 mm
Product size width	714 mm
Product size height	1,045 mm
Weight (complete product w/o side packed articles)	681 kg
Packaging length	2,251 mm
Packaging width	1,045 mm
Packaging height	714 mm
Article gross weight	6,76,000 g

SOUND AND NOISE

Sound power level, guaranteed (LWA)	100 dB(A)
Sound pressure level at operators ear (LpA)	84 dB(A)



View all product details on:

<https://www.husqvarnaconstruction.com/in/compactors/lp6500/>