



CONCRETE CORE DRILLS

HUSQVARNA DM 400

Art.no: 967 91 03 01

DM 400 is a powerful and sturdy electric core drill for medium to heavy core drilling where reliability and high productivity is needed. Recommended diameter 55-350 mm. With aluminium motor housing to withstand tough handling and a carrying handle for ergonomic usage and additional impact protection of the drill motor. Equipped with Embedded Connectivity, an enhanced version of Husqvarna Fleet Services™ for data analytics and insights into the health of the machine. Suitable for water evacuation, ventilation, angle drilling, stitch drilling and when you need to cut close to corners.

FEATURES



Sturdy and durable

Equipped with an aluminium housing and the protective carrying handle ensures rough handling.



Ergonomic

Equipped with a carrying handle for easy transport and handling.



Optimised RPM's

Enables high drilling performance.



Embedded Connectivity

An enhanced version of Husqvarna Fleet Services™. Enables data analytics and insights into the health of the machine.

TECHNICAL DATA HUSQVARNA DM 400

Art.no: 967 91 03 01

HUSQVARNA DM 400

MOTOR

Rated input power	3.2 kW
Frequency	50-60 Hz
Voltage	220-240 V
Phases	1 ph
Power Source	Corded

EQUIPMENT

Drill bit diameter with stand, max	350 mm
Recommended drill bit diameter, min	55 mm
Coolant	Wet

TRANSMISSION

Number of gearbox speeds	3
Spindle speed unloaded gear 1	420 rpm
Spindle speed unloaded gear 2	820 rpm
Spindle speed unloaded gear 3	1,250 rpm

PRODUCT DATA

Water connector	G 1 / 4"
Water pressure, max	3 bar
Spindle thread, outer	1 1/4" 7 UNC

DIMENSIONS

Product size length	546 mm
Product size width	138 mm
Product size height	185 mm
Weight (complete product w/o side packed articles)	14 kg
Packaging length	625 mm
Packaging width	255 mm
Packaging height	300 mm
Article gross weight	16,600 g

SOUND AND NOISE

Sound power level, guaranteed (LWA)	112 dB(A)
Sound power level, measured	110 dB(A)
Sound pressure level at operators ear	92 dB(A)



View all product details on:

<https://www.husqvarnaconstruction.com/in/concrete-core-drills/dm400/>

RELATED CONSUMABLES



DIAMOND CORE DRILL BITS ELITE-DRILL™ D1610

Diameter mm:
52/-/350mm
Drill connection:
1 1/4" / CR128
Core length mm:
500 mm
Coolant:
Wet



DIAMOND CORE DRILL BITS ELITE-DRILL™ D1620

Diameter mm:
52/-/350mm
Drill connection:
1 1/4" / CR128
Core length mm:
500 mm
Coolant:
Wet



DIAMOND CORE DRILL BITS ELITE-DRILL™ D1640

Diameter mm:
16/-/350mm
Drill connection:
1 1/4" / CR128
Core length mm:
500 mm
Coolant:
Wet



DIAMOND CORE DRILL BITS VARI-DRILL™ D20

Diameter mm:
16/-/300mm
Drill connection:
1 1/4"
Core length mm:
500 mm
Coolant:
Wet



DIAMOND CORE DRILL BITS VARI-DRILL™ D65

Diameter mm:
52/-/300mm
Drill connection:
1 1/4"
Core length mm:
500 mm
Coolant:
Wet



DIAMOND CORE DRILL BITS TACTI-DRILL™ D20

Diameter mm:
62/-/200mm
Drill connection:
1 1/4"
Core length mm:
500 mm
Coolant:
Wet

RELATED EQUIPMENT & ACCESSORIES



CORE DRILL STANDS DS 500

Weight (complete product w/o side packed articles):
17.6 kg
Drill bit diameter, max:
500 mm
Travel length, max:
706 mm
Column's angling:
0-90°



SLURRY RINGS/COLLECTORS SLURRY RINGS WSR

Accessory for:
Dust collectors, Drill motors



SLURRY RINGS/COLLECTORS SLURRY COLLECTOR V-SHAPED

Accessory for:
Drill stands, Drill motors, Drill motors with stand



BATTERY POWERED PRODUCTS WT 151

Battery eco system:
BLi-X
Water pressure, max:
0.9 bar
Weight (complete product w/o side packed articles):
3.6 kg
Hose length:
3 m



SLURRY RINGS/COLLECTORS SLURRY COLLECTOR



[husqvarnaconstruction.com](https://www.husqvarnaconstruction.com)