Husqvarna DM 230

Handheld electric core drill with attractive design and functional ergonomics. The motor is designed with a pistol grip giving you greater control. Handheld core drilling up to 80 mm or drilling with stand up to 150 mm. Suitable for light applications such as ventilation, plumbing pipes and electrical sockets and cables. DM 230 is an excellent choice for professionals as well as semi-professionals.

Q Drill bit **80 mm** diameter

handheld, max

O Drill bit 150 mm

diameter with stand, max

Voltage 220-240 V

Article number : DRILL MOTOR DM 230 220-240 V | 1-ph | 50 Hz | EU | 11/4" 7 - 968 41 10-01



FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



Overload protection

The machine uses pulsation to warn you of an approaching overload. If the load is not reduced the motor will shut off, to prevent overheating. Elgard™ increases productivity and extends product life.



Reliable gearbox

Watercooled 3 speed gearbox for optimal drilling performance and longer service intervals.

Easy start with reduced speed

To facilitate making a starter hole, speed is reduced by half using the Smart Start® button.

- Smooth start with normal fuses
- Dry and wet drilling
- Elgard™
- Smart Start®

Durable and ergonomic design

Durable and shock-proof, designed to protect the electronics. Easy to carry and install thanks to low weight and ergonomic design.

- Softstart™
- Barriers
- Channels, pipes and cables

SPECIFICATIONS



Water connector G 1 / 4"
Weight 7 kg
Product size length 438 mm
Product size width 104 mm



Drill bit diameter handheld, max

Drill bit diameter with stand, max

Recommended drill bit diameter, min

0 mm



Sound power level, guaranteed (LWA)

Sound power level, measured

107 dB(A)

Sound pressure level at operators ear

93 dB(A)



Number of gearbox speeds 3

Motor Motor

Electronic product Yes
Frequency 50 Hz
Voltage 220-240 V
Rated input power 1.85 kW

Specifications

Water pressure, max

Mounting collar

Spindle thread, inner

Spindle thread, outer

8 bar

60 mm

1 / 2"

1 1/4" 7 UNC