Husqvarna DM 280

Electric core drill for use with stand. The DM 280 is an ideal choice for medium core drilling up to 350 mm diameter. The motor is very easy to operate and features several ergonomic features facilitating drilling and set up. Suitable for water evacuation, ventilation, angle drilling and stitch drilling.

O Drill bit 350 mm diameter with

stand, max

Voltage 220-240 V

Article number : DRILL MOTOR DM 280 LS 220-240 V | 1-ph | 50 Hz | EU | LS - 966 55 41-01



FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



Drill with maximum pressure

A LED indicator shows the load of the machine, allowing you to always drill at maximum pressure.



Durable and ergonomic design

Durable and shock-proof, designed to protect the electronics. Easy to carry and install thanks to low weight and ergonomic design.

Reliable gearbox

Watercooled 3 speed gearbox for optimal drilling performance and longer service intervals.



Easy start with reduced speed

To facilitate making a starter hole, speed is reduced by half using the Smart Start® button.



- Elgard™
- Load indicator
- Softstart™
- Angle drilling
- Barriers

- Horizontal drilling
- Stitch drilling
- Water evacuation
- Vertical drilling
- Channels, pipes and cables

SPECIFICATIONS



Water connector G 1 / 4"
Weight 13 kg
Product size length 485 mm
Product size width 142 mm



Drill bit diameter with stand, max

Recommended drill bit diameter, min

50 mm



Electronic product Yes
Frequency 50 Hz
Voltage 220-240 V
Rated input power 2.7 kW

Specifications

Water pressure, max
Spindle thread, outer

8 bar
11/4" 7 UNC



Sound power level, guaranteed (LWA)

Sound power level, measured

112 dB(A)

Sound pressure level at operators ear

98 dB(A)



Number of gearbox speeds 3