



## DUST AND SLURRY EQUIPMENT

# HUSQVARNA T 7500

Art.no: 967 66 41 04

T 7500 is an effective industrial dust extractor to match the grinding machines Husqvarna PG 820, PG 680 and PG 400 (3-phase) as well as shavers, shot blasters and saws. Ideal for heavy-duty work and exacting demands on dust extraction. T 7500 is equipped with a quiet, yet powerful turbine motor delivering exceptional airflow. The machine can deal with materials that are difficult to handle, such as grinding dust and demolition materials in a wide variety of applications. Has a reliable filter system with high collecting efficiency and a long filter life, and can deal with large quantities of fine dust. Comes with two oversized tested and certified HEPA class H13 filters and sock-style pre-filters providing nonstop grinding and a long service life. The pre-filters can be cleaned from outside of the tank via Jet Pulse negative air pressure. The Longopac® bag hose system ensures simple, dust-free bag changes.

### FEATURES



#### Efficient filtration system

The three separate filtering stages result in longer working time between filter cleaning. The dust is filtered through a cyclone chamber, which separate the heaviest parts, up to 95% of the dust, before the washable main filter. The HEPA micro filters are individual tested and certified to capture 99.99% of the remaining silica dust in the respirable fraction (0.3µm).



#### Easy and efficient filter cleaning

The Jet Pulse filter cleaning system ensures high continuous airflow thanks to easy and efficient cleaning of the conical main filter without opening the machine.



#### Durable design

Corrosion-resistant steel clamps, welded frame with dust bag platform and durable steel handle make it ready to serve for many years.



#### Excellent stability and mobility

The slim design, solid non-marking tires, swivel casters and hitch for attaching a separator allows for excellent mobility and stability.

## TECHNICAL DATA HUSQVARNA T 7500

Art.no: 967 66 41 04

HUSQVARNA T 7500

### MOTOR

Rated input power	5.5 kW
Phases	3 ph
Voltage	400 V
Rated current	12 A
Frequency	50 Hz
Max. vacuum	280 mbar
Power source	Corded

### PRODUCT DATA

Airflow at turbine	600 m³/h
Primary filtration area	5.65 m²
HEPA Filters 99.99% at 0.3 microns	2

### DIMENSIONS

Product size length	1,245 mm
Product size width	686 mm
Product size height	1,753 mm
Weight (complete product w/o side packed articles)	206 kg
Packaging length	1,250 mm
Packaging width	690 mm
Packaging height	1,780 mm
Article gross weight	2,10,000 g



View all product details on:

<https://www.husqvarnaconstruction.com/in/dust-and-slurry-equipment/t7500/>