

Husqvarna Soff-Cut 4200

The Husqvarna 4200 self-propelled dry-cutting petrol saw has a low-noise enclosed design and is ideal for heavy-duty commercial, industrial and paving applications. The 4200 is designed for peak performance. Features include a 23 hp twin-cylinder petrol engine, three-stage cyclonic air cleaner, oil cooler, full-pressure oil lubrication, hydraulic valve lifters, mechanical fuel pump and an oil alert light. Multiple blade widths can be used, allowing different joint widths and crack control simultaneously.

- ✿ Cutting depth, max **76 mm**
- ✿ Blade diameter, max **355 mm**
- Output power **17.2 kW**
(As rated by the engine/motor manufacturer)

Article number : EARLY ENTRY SAWS Soff-Cut 4200 23 hp | 14" | CE | Kohler - 966 84 56-02



FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



Soff-Cut® technology

Husqvarna Soff-Cut® is a unique patented system for early entry concrete sawing. This technology enables concrete to be cut within the first one or two hours of finishing and before final set. Husqvarna Soff-Cut® provides the best solution for minimising the risk of random cracking, and it simplifies the working process, compared to conventional sawing. +

SPECIFICATIONS



Engine

Output power (As rated by the engine/motor manufacturer)	17.2 kW
Starter	Electric
Cylinders	2
Number of strokes	4-stroke engine



Dimensions

Weight	257 kg
Product size length	2260.6 mm
Product size height	1022.35 mm



Cutting equipment

Blade depth control	Electric
Cutting depth, max	76 mm
Blade diameter, max	355 mm