

Husqvarna PG 280

PG 280 is a single disc floor grinder that you can quickly convert for edge grinding on both sides. It efficiently grinds adhesives, paint, epoxy and spackle. With a grinding width of 280 mm it is suitable for small to medium concrete areas. Designed to facilitate an ergonomic work position, it is easy and convenient to use. The machine is light and compact and therefore easy to transport and set-up.

● Output power **1.54 kW**

(As rated by the engine/motor manufacturer)

⊕ Grinding width **280 mm**

● Phases **1 ph**

Article number : FLOOR GRINDER PG 280

220-240 V | 1-ph | 50 Hz | EU | 2-pin - 967

64 87-01



FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



Quick conversion to edge grinding

Easily removable lid covers and wheel setting enables quick conversion to edge grinding on both sides. No tools are required. Allows an upright work position.



Easy removal

Offers efficient grinding of adhesive, paint, epoxy and spackle.

Easy to transport and set-up

The machine is light and fits easily in any car thanks to the compact design and foldable frame and dividable parts.



Easy to use


The speed is fixed and no settings are required. The machine also has an user-friendly logical control panel with overload protection.



- Efficient dust management
- Time saving tool change
- Ergonomic working position


- Redi Lock®
- Hour meter
- Keep track of the edge grinding lid

SPECIFICATIONS



Motor

Output power (As rated by the engine/motor manufacturer)	1.54 kW
Rated current	13 A
Voltage	220-240 V
Phases	1 ph
Pins	2-pin
Frequency	50 Hz



Dimensions

Product size length	1320 mm
Product size width	420 mm
Product size height	990 mm
Weight	72 kg

Other

Grinding width	280 mm
Grinding disc diameter	280 mm
Grinding disc speed min	0 rpm
Grinding disc speed max	1410 rpm
Grinding pressure, max	27 kg
Direction of rotation	One Direction
Number of grinding discs	1