Husqvarna PG 530

PG 530 is a concrete floor grinder available in both 1- and 3-phase versions with high capacity. Its grinding width of 530 mm means it is excellent for residential and light commercial purposes. PG 530 combines the latest technology to deliver more power and performance than any other triple head planetary machine available in its class. Excellent choice for concrete floor preparation and repair as well as all polishing and grinding applications – both wet and dry. Perfect for HiPERFLOOR® concrete floor polishing system.

Output power 3.325 kW
(As rated by the engine/motor manufacturer)

⊚ Grinding **530 mm** width

■ Rated input 3.75 kW

power

Phases1 ph

Article number : FLOOR GRINDER PG 530 220-240 V | 1-ph | 50 Hz | CE | 2-pin - 965 19 58-11



FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



High production rate

High power machinery capable of delivering high production rates, increasing profit and saving valuable time.



Stable operation over undulating surfaces

The triple-headed grinder delivers more downward pressure and power to the grinding heads.

Gear-driven planetary head

Gear-driven planetary head; premium quality belt for powering grinding heads.



Time saving tool change

Redi Lock® is an instant and hasslefree system for changing diamond tooling.

- Ergonomic working position
- Long service intervals
- Strong durable design

- Easy to operate
- Redi Lock®

SPECIFICATIONS



3.325 kW
3.75 kW
14 A
220-240 V
1 ph
2-pin
50 Hz

Other

Number of grinding discs

Grinding width	530 mm
Grinding disc diameter	230 mm
Grinding disc speed min	200 rpm
Grinding disc speed max	900 rpm
Grinding pressure, max	134 kg
Direction of rotation	FWD/REV with
	grinding discs and
	planetary head
	rotation in same
	direction (not
	counter rotation).

3



Product size length	1100 mm
Product size width	1195 mm
Product size height	1195 mm
Weight	200 kg