Husqvarna FS 3500 G

FS 3500 G is a self-propelled floor saw ideal for small to medium patch and service jobs. Equipped with a 27.5 kW Kohler gasoline engine. It is lightweight, low profiled, easy to manoeuvre and service. The Poly-V belt together with a self-adjusting belt tensioner ensures stable power levels at the blade shaft. Cutting depth capacity up to 311 mm with a 750 mm diamond blade. Comes standard with adjustable handle bars, engine tachometer and hour meter. Water pump kit and light kit available as options.

| 🏶 Cutting | 262 mm |
|------------------|---------|
| depth, max | |
| • Output power | 27.5 kW |
| (As rated by the | |
| engine/motor | |
| manufacturer) | |
| 🐞 Blade | 650 mm |

diameter, max

Article number : FLOOR SAW FS 3500 G 37 hp | 650mm | CE | Kohler - 967 62 13-06



FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.




Automatic belt tensioner and Poly-V belt

Offers no maintenance, lower cost of ownership, consistent power and increased production.



Classic and intuitive control panel

Includes engine tachometer and water safety system.



Reduces pointer rope damage and holds front pointer at a set height.



Options include LED light-kit and water pump kit

LED offers lower electrical power consumption and water pump kit allows cutting with low water pressure and flow.



- Easy to operate
- Two-position handle bar
- Self-propelled

- Effective transfer of power to blade shaft
- Dependable design
- Flexible blade mounting

SPECIFICATIONS



| Output power (As rated by the engine/motor | 27.5 kW |
|--|-----------------|
| manufacturer) | |
| Output power at tool shaft | 21.6 kW |
| Engine cooling | Air |
| Fuel tank volume | 6.3 I |
| Cylinders | 2 |
| Number of strokes | 4-stroke engine |



Transmission speed reverse Transmission speed forward 25 m/min 51 m/min



Arbor diameter Blade depth control Blade diameter, max Cutting depth, max 25,4 mm Electric hydraulic 650 mm 262 mm



Dimensions

Product size length Product size width Product size height Weight 1168 mm 807 mm 1152 mm 450 kg