

# Husqvarna FS 4800 D

Our FS 4800 D is a very versatile diesel walk-behind flat saw ideal for asphalt and concrete cutting. Suitable for mid-sized jobs on airports and highways, as well as service work and smaller jobs that require high production rates. Cutting depth up to 381 mm. Available in front or rear pivot configurations, where the rear pivot saw is recommended when high manoeuvrability is essential.

✿ Cutting depth, max **375 mm**

● Output power **35 kW**  
(As rated by the engine/motor manufacturer)

✿ Blade diameter, max **450 mm**

Article number : FLOOR SAW FS 4800 D 48

hp | 450mm | CE | FP ETRK w/cl - 967 60

80-40



## FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



### Powerful and productive

The power transmission system with right-angle gearbox transmits high power to the blade shaft with optimum torque and minimised vibrations.



### Rear pivot version with high manoeuvrability

Ideal for road repair and service work.

### Straight and fast cuts

Our electric tracking system lets you easily make tracking adjustments while cutting.



### Low maintenance

The IntelliSeal blade shaft system allows for a minimum of 250 maintenance-free hours without daily greasing of bearings.



- Optimised cutting performance
- Adjustable handles
- Convenient transport between truck and work site
- Quick dis-engagement at blade slam
- Easy to operate

- Comprehensive control panel
- Automatic depth stop
- Highly versatile 3-speed version
- Self-propelled

## SPECIFICATIONS



### Engine

Output power (As rated by the engine/motor manufacturer)	<b>35 kW</b>
Output power at tool shaft	<b>35.3 kW</b>
Engine cooling	<b>Liquid /Air</b>
Fuel tank volume	<b>29.53 l</b>
Cylinders	<b>4</b>
Number of strokes	<b>4-stroke engine</b>



### Transmission

Transmission speed forward	<b>60.96 m/min</b>
----------------------------	--------------------



### Cutting equipment

Arbor diameter	<b>25,4 mm</b>
Blade depth control	<b>Electrohydraulic</b>
Blade diameter, max	<b>450 mm</b>
Cutting depth, max	<b>375 mm</b>



### Dimensions

Product size length	<b>1422.4 mm</b>
Product size height	<b>1295.4 mm</b>
Weight	<b>680 kg</b>