

Husqvarna FS 7000 D

Our modern FS 7000 D is a powerful diesel walk-behind floor saw with low emissions compliant with Tier 4 and Stage IIIB regulations. The product's size, weight and balance is optimised for high production in applications cutting asphalt and concrete. With an impressive level of sustainable torque from the Deutz turbo diesel engine, it maximise production rates in the toughest conditions and contributes to a healthier working environment. The modern, service-friendly design, ergonomic controls and electronic support systems are highly intuitive, with focus on operator efficiency and convenience. The product is available with single speed or with 3-speed gearbox, as well as blade clutch, electronic tracking system on the rear axle, 5th wheel, light kit, water pump kit and weight kits.



✿ Cutting **411 mm**

depth, max

● Output power **55.4 kW**

(As rated by the
engine/motor
manufacturer)

✿ Blade **900 mm**

diameter, max

Article number : FLOOR SAW FS 7000 D 74

hp | 36" | Deutz | FP - 967 20 79-15

FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



Powerful and fuel-efficient

Common-rail diesel engine with low emissions.



Low emissions

Equipped with diesel particle filter (DPF). Complies with Stage IIIB / Tier 4 regulations.

Intuitive and ergonomic control panel

All important functions are easy to reach and monitor, such as blade rpm, forward speed, electronic tracking, depth gauge, belt and pulley ratios, runtime and service minder. +



Easy adjustment of tracking for straight cuts

Electric tracking system includes position indicator on the display, it can automatically return to neutral position and has the ability to memorise last used setting.



- Powerful and productive
- Ergonomic
- Adjustable and telescopic pointer
- Adjustable handles
- Convenient transport between truck and work site
- Quick dis-engagement at blade slam
- Easy assembly of blade guard

- Easy to operate
- Optimised display visibility
- Automatic depth stop
- Low maintenance
- Highly versatile 3-speed version
- Self-propelled
- Optimised weight distribution

SPECIFICATIONS



Engine

| | |
|--|------------------------|
| Output power (As rated by the engine/motor manufacturer) | 55.4 kW |
| Output power at tool shaft | 54.4 kW |
| Engine cooling | Liquid /Air |
| Fuel tank volume | 40 l |
| Cylinders | 4 |
| Number of strokes | 4-stroke engine |




Transmission

| | |
|----------------------------|-----------------|
| Transmission speed reverse | 0 m/min |
| Transmission speed forward | 76 m/min |



Cutting equipment

| | |
|---------------------|----------------------|
| Arbor diameter | 25,4 mm |
| Blade depth control | Electro hydro |
| Blade diameter, max | 900 mm |
| Cutting depth, max | 411 mm |



Dimensions

| | |
|---------------------|----------------|
| Product size length | 1961 mm |
| Product size width | 974 mm |
| Product size height | 1499 mm |
| Weight | 1032 kg |