



POWER CUTTERS

HUSQVARNA K/4000

Art.no: 967 07 98 01

This electric all-round cutter minimises the amount of water and slurry. Unlike other electric cutters, the blade rotates forward, cutting into the material efficiently with minimum effort on the operator. K/4000 is easily adaptable for dry cutting with the Vac attachment accessory for minimal dust generation.

FEATURES

Perfect for indoor use

A powerful electric cutter for both indoor and outdoor use.

Overload protection

Our Elgard system protects against overload by varying the rotation speed.

High durability and low noise levels

Generously dimensioned mitre gear provides high durability, minimal power loss and low noise levels.

"Pulling" rotation

The blade on all our electric cutters rotates forward, cutting into the material efficiently, minimising the risk of sticking and kickbacks.



TECHNICAL DATA HUSQVARNA K/4000

Art.no: 967 07 98 01

HUSQVARNA K/4000

ENGINE

Power source	Corded
--------------	--------

MOTOR

Rated input power	2.7 kW
Frequency	50-60 Hz
Phases	1 ph
Voltage	220-240 V

CUTTING EQUIPMENT

Cutting depth, max	125 mm
Blade diameter, max	350 mm
Arbor diameter	25.4 mm
Blade thickness, max	5.6 mm
Peripheral speed, max	100 m/s
Coolant	Wet /dry

DIMENSIONS

Product size length	631 mm
Product size width	221 mm
Product size height	313 mm
Weight (complete product w/o side packed articles)	7.6 kg
Packaging length	740 mm
Packaging width	240 mm
Packaging height	340 mm
Article gross weight	10,700 g

SOUND AND NOISE

Sound power level, guaranteed (LWA)	105 dB(A)
Sound pressure level at operators ear (LpA)	95 dB(A)

VIBRATION

Vibrations left/front handle	3.5 m/s ²
Vibrations right/rear handle	3.5 m/s ²

CERTIFICATIONS

Cert machine dir. 2006/42/EC Decl. No.	CB SE-89319
--	-------------



View all product details on:

<https://www.husqvarnaconstruction.com/in/power-cutters/k4000/>



Husqvarna

© 2025 Husqvarna AB. All rights reserved. Specifications subject to change without notice.

RELATED EQUIPMENT & ACCESSORIES




POWER CUTTER BLADES ELITE-CUT™ S85

Diameter mm:
300 / 350 / 400 mm

Segment height mm:
12 mm

Arbor diameter:
25.4/20 mm



POWER CUTTER BLADES VARI-CUT™ S50

Diameter mm:
400 mm

Segment height mm:
12 mm

Arbor diameter:
25.4/20 mm

RELATED CONSUMABLES



BATTERY POWERED PRODUCTS WT 15I

Battery eco system:
BLI-X

Water pressure, max:
0.9 bar

Weight (complete product w/o side packed articles):
3.6 kg

Hose length:
3 m



WATER TANKS WT 10 MP

Water Tank Capacity:
10 l

Weight (complete product w/o side packed articles):
2.35 kg



Husqvarna