



POWER CUTTERS

HUSQVARNA K 770

Art.no: 967 68 21 01

The Husqvarna K 770 is a powerful all-round power cutter with features that make it one of the best power cutters on the market. Equipped with semi-automatic SmartTension™ system allows for optimal power transmission, minimum wear and maximum belt life. The light weight, outstanding power-to-weight ratio, the reliable start and exceptionally low vibrations mean less strain and maximised productivity. Suitable for road work and easy to cut in a straight or curved track or close to sidewalk when used with KV7 trolley.

FEATURES



Easy and optimal belt tensioning

The semi-automatic SmartTension minimises the risk of underand over tensioning

Light and powerful

A light, compact and powerful machine with superior power-to-weight ratio.

Exceptionally low vibrations

Vibrations below 2.5 m/s² in the cutter handles for more comfort and longer operation periods.



Long service intervals

A strong Poly-V belt combined with our maintenance-free starter DuraStarter™ and efficient filter-system Active Air Filtration™ ensures long service intervals.

TECHNICAL DATA HUSQVARNA K 770

Art.no: 967 68 21 01

HUSQVARNA K 770

ENGINE

Output power	3.7 kW
Max engine/motor	9,300 rpm
Maximum power speed	9,000 rpm
Cylinders	1
Number of strokes	2-stroke engine
Exhaust emissions (CO, EU V)	711 g/kWh
Power source	Petrol

CUTTING EQUIPMENT

Cutting depth, max	125 mm
Blade diameter, max	350 mm
Arbor diameter	25.4/20 mm
Blade thickness, max	5 mm
Peripheral speed, max	90 m/s
Coolant	Wet

DIMENSIONS

Product size length	605 mm
Product size width	225 mm
Product size height	415 mm
Weight (complete product w/o side packed articles)	10.1 kg
Packaging length	700 mm
Packaging width	250 mm
Packaging height	430 mm
Article gross weight	12,900 g

SOUND AND NOISE

Sound power level, guaranteed (LWA)	115 dB(A)
Sound pressure level at operators ear (LpA)	101 dB(A)

VIBRATION

Vibrations left/front handle	2 m/s ²
Vibrations right/rear handle	2.3 m/s ²



View all product details on:


<https://www.husqvarnaconstruction.com/in/power-cutters/k770/>

RELATED CONSUMABLES




POWER CUTTER BLADES ELITE-CUT™ S85

Diameter mm:
300 / 350 / 400 mm
Segment height mm:
12 mm
Arbor diameter:
25.4/20 mm




POWER CUTTER BLADES VARI-CUT™ S50

Diameter mm:
400 mm
Segment height mm:
12 mm
Arbor diameter:
25.4/20 mm



POWER CUTTER BLADES TACTI-CUT™ S50

Diameter mm:
350 mm
Segment height mm:
10 mm
Arbor diameter:
25.4/20 mm



POWER CUTTER BLADES TACTI-CUT™ S50 PLUS

Diameter mm:
400 mm
Segment height mm:
13 mm
Arbor diameter:
25.4/20 mm



POWER CUTTER BLADES TACTI-CUT™ S65

Diameter mm:
350 / 400 mm
Segment height mm:
10 mm
Arbor diameter:
25.4/20 mm

RELATED EQUIPMENT & ACCESSORIES



WATER TANKS WT 15I

Water pressure, max:
0.9 bar
Water Tank Capacity:
15 l
Weight (complete product w/o side packed articles):
3.6 kg
Hose length:
3 m



WATER TANKS WT 10 MP

Water Tank Capacity:
10 l
Weight (complete product w/o side packed articles):
2.35 kg



husqvarnaconstruction.com