

Husqvarna K 1270 Rail

Cutting a rail track takes power, precision and speed. The K 1270 Rail is the market's most powerful cutter, customised for railways, tram tracks and metro systems. It cuts fast and straight, the attachment mounts quickly to the rail and the double attachment mountings means you can cut from any direction.

- ✿ Cutting depth, **118 mm**
max
- ✿ Blade **350 mm**
diameter, max
- Output power **5.8 kW**

Article number : POWER CUTTER K 1270 Rail

14" | 1" | RA10 - 967 98 19-01



FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



Easy to start

The unique design of the carburettor, cylinder and digital ignition system, together with air purge and decompression valve ensure an easy start.



Anti-vibration system

Reduced vibrations in the cutter handle for more comfort and longer operation periods.

Perfect right-angle cuts

The RA 10 attachment fastens to the track to ensure a perfect right-angle cut.



Cutting from both sides

The RA 10 attachment is included as standard and allows cutting from both sides of the track.



- Fast, stable mounting
- Superior power with low emissions
- Reduced wear
- Maintenance-free air filter

- Active Air Filtration™
- SmartCarb™
- Poly-V belt
- Wet cutting kit

SPECIFICATIONS

Engine

Output power	5.8 kW
Cylinder displacement	118.8 cm³
Electrode gap	0.5 mm
Cylinders	1
Number of strokes	2-stroke engine
Exhaust emissions (CO2 EU V)	726 g/kWh

Dimensions

Product size length	742 mm
Product size width	241 mm
Product size height	439 mm
Weight	15.3 kg

Vibrations

Vibrations left/front handle	3.4 m/s²
Vibrations right/rear handle	3.5 m/s²

Cutting equipment

Cutting depth, max	118 mm
Blade diameter, max	350 mm
Arbor diameter	25,4 mm
Blade thickness, max	5 mm
Peripheral speed, max	90 m/s

Sound and noise

Sound power level, guaranteed (LWA)	117 dB(A)
Sound pressure level at operators ear	104 dB(A)

Certifications

Cert machine dir. 2006/42/EC Decl. No.	SEC/10/2287
----------------------------------------	--------------------