Husqvarna K 970

Sturdy, reliable, light and powerful - the K 970 power cutter is ready to perform when you are. The ultimate choice when you need an all-round cutter performing in the toughest conditions, withstanding climate and fuel variations. Suitable for road works when used with the corresponding KV 970 trolley. The trolley also means you can fully concentrate on the cutting job.

#I Cutting depth, 125 mm

max

Blade 350 mm diameter, max

• Output power 4.8 kW

Article number : POWER CUTTER K 970 14" | 20mm/1" - 967 34 80-01



FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



Easy and optimal belt tensioning

The semi-automatic SmartTension minimises the risk of under- and over tensioning.



Sturdy and reliable

Less sensitive to outer conditions and fuel variations, thanks to the cylinder design and muffler with integrated heat deflector.

Easy to start

The unique design of the carburettor, cylinder and digital ignition system, together with air purge and decompression valve ensure an easy start.



Long service intervals

A strong Poly-V belt combined with our maintenance-free starter DuraStarter™ and efficient filtersystem Active Air Filtration™ ensures long service intervals.



- Maintenance-free starter
- Less emissions and fuel consumption
- Cuts close to walls or ground
- Active Air Filtration[™]
- Anti-vibration system
- DuraStarter™
- Poly-V belt
- Reversible cutting arm
- SmartCarb™
- Wet cutting kit

- Less slurry and low water consumption
- Magnesium blade guard
- Decreased weight
- Light and powerful
- Easy to change blade guard position
- Fits multiple blade bushings
- Maintenance-free air filter
- High power with less fuel
- Reduced wear
- Blade retarder


SPECIFICATIONS



Output power Cylinder displacement Electrode gap Cylinders Number of strokes Exhaust emissions (CO2 EU V)



Product size length Product size width Product size height Weight



Vibrations left/front handle Vibrations right/rear handle 4.8 kW 93.6 см³ 0.5 mm 1 2-stroke engine 736 g/kWh

661 mm

214 mm

444 mm

3.8 m/s²

4.2 m/s²

11 kg



Cutting depth, max125 mmBlade diameter, max350 mmArbor diameter20/25,4 mmBlade thickness, max5 mmPeripheral speed, max90 m/s



Sound power level, guaranteed (LWA)	115 dB(A)
Sound pressure level at operators ear	104 dB(A)

Certifications

Cert machine dir. 2006/42/EC Decl. No.

EURO TEST CERTIFICATE SEC/10/2286