

## Husqvarna PP 455 E

The electrically powered hydraulic unit PP 455 E is specially developed for the WS 463 wall saw and the CS 2512 wire saw. It's equipped with a water-cooled electric motor providing more efficient sawing, enabling you to work at full capacity for the entire saw process. The electric motor is mounted beneath the tank, providing a low centre of gravity and good stability.

- Hydraulic oil flow **65 l/min**
- Hydraulic pressure, max **230 bar**
- Rated current **63 A**
- ⚡ Voltage **400 V**

Article number : POWER PACK PP 455 E

400V | 50Hz | 4-pin | w. Radio - 965 15 66-

02



## FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



### Maximum machine life and power

Hydraulic oil is cooled by a large, 15-litres oil reservoir and 23 cm fan to provide maximum machine life and power.



### Adjustable handles

The handles are vertically adjustable and the power pack can be laid down on its handles during transport as well as operation.

### Easy hose connection

Pressure compensation system makes it easy to connect the hoses with less effort.

- Easy transportation together with wall saw
- Easy transportation and positioning

### 230 V power outlet

For connection of peripheral equipment (when using 5-pin, 3-phase system).

- Water-cooled heat exchanger
- Flexible power setup

## SPECIFICATIONS



|  |              |
|--|--------------|
| Output power (As rated by the engine/motor manufacturer) | <b>25 kW</b> |
| Rated current  | <b>63 A</b>  |
| Voltage  | <b>400 V</b> |



|        |               |
|--------|---------------|
| Weight | <b>139 kg</b> |
|--------|---------------|

## Hydraulics

|                         |                 |
|-------------------------|-----------------|
| Oil capacity            | <b>16 l</b>     |
| Hydraulic oil flow      | <b>65 l/min</b> |
| Hydraulic pressure, max | <b>230 bar</b>  |