### Husqvarna WS 440 HF

WS 440 HF electric wall saw gives you increased possibilities for fast and efficient cutting in reinforced concrete, brick and other building materials, up to 530 mm thickness. Use this wall saw for all kinds of openings and sawing including stair, bevel and flush cutting. The user-friendly ergonomic design and ease of transport makes your job fast and efficient. WS 440 HF can be combined with CS 10, transforming it into a perfect wire saw.

Blade 600 mm

diameter, min

Blade 1200 mm

diameter, max

# Cutting depth, 530 mm

max

Article number: WALL SAW WS 440 HF 800

mm - 967 64 66-02



#### **FEATURES**

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



# Impressive power to the spindle

The strong motor produces high power to the spindle, even though the saw is light.

### Deep cutting depth, even with starter blade

Large maximum starter blade enables deep cutting without changing blades.

- Easy attachment of saw
- Quick and easy change of blade direction
- User-friendly wireless remote control
- Easy to change blades
- Sawing on both sides of the track
- Straight cuts with minimal wear
- Efficient and fast sawing
- Optimised speed for each cutting application



# Easy to transport and setup

The saw's modular design and even weight distribution make it easy to carry and handle.

## Retains high power for efficient sawing

Highly efficient electric motor retains high power to the spindle over a wide rpm range. Minimum water needed for cooling, which means less slurry.

- Durable and light blade guard
- Door openings
- Window openings
- Ventilation channels
- Special cutting
- Dovetail cutting
- Flush cutting

#### **SPECIFICATIONS**



Output shaft RPM, max

Max spindle torque

Spindle starting torque, Nm

1200 rpm

125 Nm

100 Nm

1



Number of gearbox speeds



Sound power level, guaranteed (LWA)

Sound power level, measured

108 dB(A)

Sound pressure level at operators ear

108 dB(A)



Arbor diameter 25,4/60 mm

Blade diameter, max 1200 mm

Blade diameter, min 600 mm

Cutting depth, max 530 mm

Starter blade diameter, max 1000 mm



Product size length
Product size width
Product size height
Weight
Weight saw carriage
Weight saw unit

2200 mm
800 mm
800 mm
25 kg
Weight saw carriage
3.9 kg
25 kg

### **Other**

Water flow, min
Water pressure, max
Water temp at min flow, max

3.5 I/min
7 bar
25 °C