

Husqvarna WS 463

WS 463 hydraulic wall saw is very powerful and is designed to make your work more efficient. Use it to cut reinforced concrete, brick and other building materials, up to 730 mm thickness. It can be used for all kinds of openings and sawing including stair, bevel and flush cutting.

- 🌀 Blade **600 mm**
diameter, min
- 🌀 Blade **1600 mm**
diameter, max
- 🌀 Cutting depth, **730 mm**
max

Article number : WALL SAW WS 463 800 mm

| 25.4/6 mm - 965 15 60-01



FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



Deep cutting depth, even with starter blade

Large maximum starter blade enables deep cutting without changing blades.

Sawing on both sides of the track

Versatile and efficient setup with symmetric track and carriage.

- Easy to transport and setup
- Easy attachment of saw
- Easy to change blades
- Door openings
- Window openings



Durable and light blade guard

Made of aluminum, extremely durable, light and easy to install.

Straight cuts with minimal wear

Small distance between track and blade gives a straight cut, generating minimal wear on both saw and blade.

- Ventilation channels
- Special cutting
- Dovetail cutting
- Flush cutting



SPECIFICATIONS



Motor

Output shaft RPM, max	14000 rpm
Max spindle torque	350/200/120

Hydraulics

Hydraulic oil flow	65 l/min
Hydraulic pressure, max	230 bar



Dimensions

Weight saw carriage	22 kg
Weight saw unit	22 kg

Other

Water pressure, max	7 bar
---------------------	--------------



Cutting equipment

Arbor diameter	25,4/60 mm
Blade diameter, max	1600 mm
Blade diameter, min	600 mm
Cutting depth, max	730 mm
Starter blade diameter, max	1000 mm



Transmission

Number of gearbox speeds	3
--------------------------	----------



Sound and noise

Sound power level, measured	117.8 dB(A)
Sound pressure level at operators ear	100.3 dB(A)