

## WIRE SAWS

# HUSQVARNA CS 10

Art.no: 966 56 57 01

CS 10 is a very useful and efficient saw system, thanks to a number of smart solutions. The saw is designed to be combined with our electric wall saws WS 482 HF or WS 440 HF, giving you a flexible wall and wire saw in one single system. Use it for both small and large jobs sawing in steel, concrete and other building materials. The symmetrical design lets you use the machine in all positions and even reaches into the tightest spots.

## FEATURES



### Easy handling

Its compact design makes CS 10 easy to operate, transport and store.



### Highly efficient and flexible

Possible to saw both vertically and horizontally. The saw head can be mounted on either side of the track and the direction of the wire is reversible.



### User-friendly wireless remote control

Together with WS 482 HF or WS 440 HF, you can use a remote control, that has a logical and ergonomic design with a large and clear display, which shows the current performance of the saw.



### Efficient product fleet

Thanks to compatibility between wall and wire systems.

## TECHNICAL DATA HUSQVARNA CS 10

Art.no: 966 56 57 01

HUSQVARNA CS 10

### ENGINE

|   |                   |
|---|-------------------|
| Motor for wire drive                      | Electric Wall Saw |
| Output power with WS 482 HF and PP 492    | 19 kW             |
| Output power with WS 482 HF and PP 490    | 19 kW             |
| Output power with WS 482 HF and PP 480 HF | 19 kW             |
| Output power with WS 440 HF and PP 492    | 13 kW             |
| Output power with WS 440 HF and PP 440 HF | 13 kW             |
| Spindle starting torque                   | 160 Nm            |
| Power Source                              | Corded            |

### CUTTING EQUIPMENT

|                        |        |
|------------------------|--------|
| Wire speed gear 2, max | 24 m/s |
|------------------------|--------|

### PRODUCT DATA


|                                       |                 |
|---------------------------------------|-----------------|
| Direction of rotation                 | Both directions |
| Wire configuration in drive unit, min | 1 m             |
| Net wire storage capacity             | 10 m            |

### DIMENSIONS

|  |            |
|--|------------|
| Product size length                                | 1,200 mm   |
| Product size width                                 | 800 mm     |
| Product size height                                | 5,400 mm   |
| Weight (complete product w/o side packed articles) | 100 kg     |
| Weight with WS 440 HF                              | 135 kg     |
| Weight with WS 482 HF                              | 138 kg     |
| Packaging length                                   | 800 mm     |
| Packaging width                                    | 1,200 mm   |
| Packaging height                                   | 1,310 mm   |
| Article gross weight                               | 1,88,800 g |

### SOUND AND NOISE

|                                       |           |
|---------------------------------------|-----------|
| Sound power level, guaranteed (LWA)   | 100 dB(A) |
| Sound power level, measured           | 99 dB(A)  |
| Sound pressure level at operators ear | 86 dB(A)  |



View all product details on:

<https://www.husqvarnaconstruction.com/in/wire-saws/cs10/>



**DIAMOND WIRES**  
**ELITE-WIRE™ C1000**

**Coolant:**  
Wet /dry  
**Number of beads mm:**  
44  
**Bead diameter mm:**  
10.3 mm  
**Assembly:**  
Springs + rubber, vacuum brazed



**DIAMOND WIRES**  
**VARI-WIRE™ C890**

**Coolant:**  
Wet  
**Number of beads mm:**  
40  
**Bead diameter mm:**  
11 mm  
**Assembly:**  
Spring + rubber, hybrid beads



**DIAMOND WIRES**  
**TACTI-WIRE™ C790**

**Coolant:**  
Wet  
**Number of beads mm:**  
40  
**Bead diameter mm:**  
11 mm  
**Assembly:**  
Springs + rubber, sintered beads