

Husqvarna CS 10

The CS 10 is a very useful and efficient saw system, thanks to a number of smart solutions. The saw is coupled to our electric wall saws WS 482 HF or WS 440 HF. It can be mounted on both sides of the track, and the wire's direction of rotation is reversible. You can saw both vertically and horizontally. Plus there's no need for water for dry cuts in cases when slurry is a concern.

- Net wire **10 m**
storage capacity
- Output power **13 kW**
with WS 440 HF
and PP 440 HF
- Output power **19 kW**
with WS 482 HF
and PP 480 HF
- Weight with **135 kg**
WS 440 HF

Article number : WIRE SAW CS 10

EU/US/RoW | Swivel pullies - 966 56 57-01



FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



Easy handling

Its compact design makes CS 10 easy to operate, transport and store.



Highly efficient and flexible

Possible to saw both vertically and horizontally. The saw head can be mounted on either side of the track and the direction of the wire is reversible.

User-friendly wireless remote control

Together with WS 482 HF or WS 440 HF, you can use a remote control, that has a logical and ergonomic design with a large and clear display, which shows the current performance of the saw. +



Efficient product fleet

Thanks to compatibility between wall and wire systems.



- Flexible installation

- Flexible operation

SPECIFICATIONS



Engine

Motor for wire drive	Electric Wall Saw
Output power with WS 440 HF and PP 440 HF	13 kW
Output power with WS 482 HF and PP 480 HF	19 kW
Output power with WS 482 HF and PP 490	25 kW
Spindle starting torque, Nm	160 Nm



Sound and noise

Sound power level, guaranteed (LWA)	100 dB(A)
Sound power level, measured	99 dB(A)
Sound pressure level at operators ear	86 dB(A)



Dimensions

Weight	100 kg
Weight with WS 440 HF	135 kg
Weight with WS 482 HF	138 kg

Other

Direction of rotation	Both directions
Wire configuration in drive unit, min	1 m
Net wire storage capacity	10 m