

Husqvarna CS 2512

CS 2512, in combination with the hydraulic unit PP 455 E, is a powerful and easy to use wire saw. It is compact and mobile for smaller jobs but can also handle very large deep sawing jobs. It can be used for a wide range of applications, both on the ground or mounted on walls. Use it for sawing in steel, concrete and other building materials.

- Wire speed **20 m/s**
gear 1, max
- Wire speed **25 m/s**
gear 2, max
- Net wire **16 m**
storage capacity

Article number : WIRE SAW CS 2512

Wiresaw - 965 15 62-01



FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



Large wire magazine

Although the wire saw is compact it has a large magazine capacity, enabling larger cuts without cutting the wire.

Flexible setup

Thanks to modular systems, the wire saws are easy to install. They can be positioned both vertically and horizontally. The motor can be detached for easier transportation.

Easy transportation

Practical collapsible handles and foldable guard allow easy transportation of the unit. The saw can also be dismantled into sections, which further increases mobility.

- Tightened wire in the magazine
- Easy to control wire tension
- Larger jobs



Smooth cutting

The pulleys follow the direction of the wire automatically thanks to the ball bearing turning mechanism.

- Thick walls
- Confined spaces



SPECIFICATIONS

Engine

Motor for wire drive

Spindle starting torque, Nm

Hydraulics

Hydraulic oil flow

Hydraulic pressure, max

Sound and noise

Sound power level, guaranteed (LWA)

Sound power level, measured

Sound pressure level at operators ear

Hydraulic multiple gear
190

65 l/min
230 bar

95 dB(A)

94 dB(A)

83 dB(A)

Cutting equipment

Wire speed gear 1, max

Wire speed gear 2, max

20 m/s

25 m/s

Dimensions

Weight

150 kg

Other

Direction of rotation

Wire configuration in drive unit, min

Net wire storage capacity

One Direction

3.4 m

16 m