

Movitec B

Vertical High-pressure in-line pumps

Applications:

- RO Plants
- Irrigation systems
- Washing plants
- Pressure boosting
- Industrial plants
- Water supply systems
- Heating, ventilation and air-conditioning systems
- Marine applications



Movitec B - Vertical High-pressure in-line pumps

Energy-efficient

- Higher efficiencies
- Very low NPSH values
- Maximum energy efficiency at full transparency of pump operation with PumpDrive*

Flexible

Large variety of materials and connections as well as extended temperature and pressure range.

Reliable

Product-lubricated plain bearing of tungsten carbide, cast pump foot, torsion-resistant pump shroud and conned O-ring.

Easy to service

- Can be fitted with any standardised mechanical seal (to EN12756).
- Can be fitted with Easy Access and cartridge seals allowing quick replacement.



Corrosion-resistant hydraulic components made of stainless steel.



Technical data

Movitec	VC, V, VS	LHS6*		
Discharge m³/h	22 (up to 112.8*)	8.6		
Head m	249 (up to 255*)	380		
Max. pressure bar	25 (up to 40*)	40		
Fluid temperature in °C	-20 to +140	-15 to +120		

^{*} Can be made available from KSB Netherlands on request

Materials of construction

	Materials			Sizes 2/4/6/10/15/ 25*/40*/60*/90*			Other sizes
	Description	Grade (India)	Grade (Europe)	VC	V	VS	LHS6*
Pump casing	Cast iron	IS210 FG 260	JL1040	х			
	Cast stainless steel	A743 CF8	1.4308		х		
	Cast stainless steel	A743 CF8M	1.4408			х	х
Hydraulic system	Stainless steel	1.4301	1.4301	х	х		
	Stainless steel	1.4404	1.4404			х	х
	Cast stainless steel 1)		1.4308	х	х		
	Cast stainless steel 1)		1.4408			х	
	Cast iron	IS210 FG 260	JS1030/JL1040		х	х	
	Cast stainless steel		1.4308		o*	0*	



- x Standard (pre-configured model)
- * Can be made available from KSB Netherlands on request



Round flange Movitec VCF



Round flange Movitec VF



Oval flange Movitec V



Victaulic coupling Movitec V(S)V



External thread connector Movitec VE

Triclamp coupling Movitec V(S)T





Mumbai-Pune Road, Pimpri, Pune - 411 018. India. Tel.: +91 20 2710 1000 Fax: +91 20 2742 6000 www.ksbindia.co.in